



## Method for manufacturing screen plate and screen plate

### BACKGROUND OF THE INVENTION

This invention relates to the method for manufacturing of a screen plate and the screen plate that prevent generating of moire such as moire fringes, spot and so on in a screen printing.

Conventionally, the number of lines of a screen are 300 lines/inch in the case of the printed matter of a screen-printing, and the screen angle between each color plate is set into 30 degree's difference. The color of yellow is set at 15 degree's difference, for example, 0 degree, 60 degree and so on.

In the conventional manufacture method of the screen plate, the moire such as moire fringes and a spot is generated in the relation with the number of screen lines and a screen angle.

SUMMARY OF THE INVENTION

In light of the forgoing, it is an object of the invention to provide a the method for manufacturing of a screen plate and the screen plate which can prevent certainly the generating of moire and print a picture with a lively motion  
5 and with high resolution. It is another object of the invention to provide a method for manufacturing of a screen plate and the screen plate that can be manufactured the high utility value of a screen plate in the optimal state.

Novel features which are believed to be characteristic of the invention, both as to its organization and method of operation, together with further objects  
10 and advantages thereof, are described below with reference to the accompanying drawings in which preferred embodiments of the invention are illustrated as an example.

It is to be expressly understood, however, that the drawings are for the purpose of illustration and description only, and are not intended as a definition of  
15 the limits of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a flow chart showing a first embodiment of the present invention;

FIG. 2 is ~~an explanation view~~ a chart showing screen angle of a degree of  
5 a screen;

FIG. 3 is ~~an explanation view~~ another chart of another degree of a screen;

FIG. 4 is ~~an explanation view~~ a diagram of a step for forming a screen  
10 plate;

FIG. 5 is ~~an explanation view~~ a diagram showing the way in which a T-shirt is printed;

FIG. 6 is ~~an explanation view~~ a diagram showing the way in which a can is printed;

FIG. 7 is a flow chart showing a second embodiment of the present invention;

FIG. 8 is ~~an explanation view~~ a diagram of a process for forming a screen plate;

5 FIG. 9 is a flow chart showing a third embodiment of the present invention;

FIG. 10 is ~~an explanation view~~ a diagram when the pattern as a manuscript is read with a scanner;

FIG. 11 is a view about a moire prevention process;

10 FIG. 12 is ~~an explanation view~~ a diagram for performing from a digital decomposition to a monochrome-two gray scale;

FIG. 13 is ~~an explanation view~~ a diagram for performing from gray scale

conversion to a finishing;

FIG. 14 is a reference view for receiving the data of picture;

FIG. 15 is a flow chart showing a fourth embodiment of the present invention;

5 FIG. 16 is ~~an explanation view~~ a diagram of a step for selecting;

FIG. 17 is ~~an explanation view~~ a diagram of a step for selecting a color;

FIG. 18 is ~~an explanation view~~ a diagram of a step for performing the spot color;

FIG. 19 is ~~an explanation view~~ a diagram of a step for converting;

10 FIG. 20 is ~~an explanation view~~ a diagram of a step for processing a frame;

FIG. 21 is a flow chart showing a fifth embodiment of the present

invention;

FIG. 22 is ~~an explanation view~~ a diagram of a step for processing an  
operation;

FIG. 23 is ~~an explanation view~~ a diagram of a step for saving;

5 FIG. 24 is ~~an explanation view~~ a diagram of a step for amending;

FIG. 25 is a flow chart showing a sixth embodiment of the present  
invention;

FIG. 26 is ~~an explanation view~~ a diagram of a step for forming an under  
base white;

10 FIG. 27 is ~~an explanation view~~ a diagram of a step for forming a top  
white;

FIG. 28 is ~~an explanation view~~ a diagram of a step for forming an under

MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

base white;

FIG. 29 is ~~an explanation view~~ a diagram of a step for forming an under  
base white;

FIG. 30 is ~~an explanation view~~ a diagram of a step for forming a top  
5 white;

FIG. 31 is ~~an explanation view~~ a diagram of a step for converting an index  
color;

FIG. 32 is ~~an explanation view~~ a diagram of a step for determining the  
number of colors;

10 FIG. 33 is ~~an explanation view~~ a diagram of a step for adding the colors;

FIG. 34 is ~~an explanation view~~ a diagram of a step for processing the  
index color;

FIG. 35 is ~~an explanation view~~ a diagram of a step for reversing; and

FIG. 36 is ~~an explanation view~~ a diagram of a step for converting.

# DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention are described in more  
 5 detail below with reference to the accompanying drawings.

An understanding of the present invention may be best gained by  
 reference to FIGS. 1-6

~~In the~~ Referring to Figs. 1 - 6 and 10, according to a first  
embodiment of a method for manufacturing a screen plate according to the  
 10 present invention, the method for manufacturing the screen plate printed as a net  
 positive by ~~the same~~ a conventional method ~~as usual~~ after ~~the manuscript~~ an  
image to be printed is suitably processed ~~suitably~~ by using a scanner X and  
 changed to the ~~the~~ digital image data which can ~~proceed by using the scanners X~~  
be processed for plate-making, by a computer or the like ~~and~~ is produced as a



separation net negative (net negative) and which is ~~proceeded to reverse the net~~  
~~negative~~ reversed to a net positive image when adhesively applied to the object  
being printed[[, the]] Reference numeral 1 shows a step for preventing [[a]]  
 moire. In a first phenomenon part aspect of the invention, as shown in a graph  
 5 having [[a]] X and Y ~~axles~~ axes for example, as shown in Fig. 2, a screen dot  
 angle ~~of for~~ cyan 2 is set at 79 to 81 degrees, preferably 80  
~~degree~~ degrees; the screen dot angle ~~of for~~ black 3 is set at 51 to 53 degrees,  
 preferably 52 ~~degree~~ degrees; a screen dot angle ~~of for~~ magenta 4 is set at 21 to  
 23 degrees, preferably 22 ~~degree~~ degrees; and a screen dot angle ~~of for~~ yellow  
 10 is set at 6 to 8 degrees, preferably 7 ~~degree~~ degrees. Then spots 6 that are  
 formed in the shape of an ellipse are used.

In addition, each screen dot angle in the first phenomenon part aspect of  
the invention which is set up in the first embodiment is also positioned at a  
 second, third and fourth phenomenon parts as an opposite angle or a symmetrical  
 15 angle. For example, as shown in FIG. 3, in the second phenomenon part, cyan 2 is  
 set up at 170 degrees; black 3 is set up at 142 degrees; magenta 4 is set up at 112  
 degrees; and yellow 5 is set up at 97 degrees.

Moreover, the screen dot angle that prevents the moire ~~generating~~  
generation of the spots etc. may be, for example, set up at approximately 6 to 8  
degrees of for cyan 2; approximately 66 to 68 degrees of for black 3;  
approximately 126 to 128 degrees of for magenta 4; and approximately 170 to  
5 173 degrees of for yellow 5. Also each color's screen dot angle that prevents to  
generate the moire can be set up freely or alternatively.

The numeral 7 shows a step for forming a screen plate 11. As shown in  
FIG. 4, the screen plate 11 includes a screen 9 having a positive film 8 having an  
arbitrary numbers of screen lines, 240 lines in this embodiment and a frame 10  
10 made from aluminum, stretching the screen 9 in the level and the perpendicular  
state by the same method as usual. In this embodiment, the screen 9 is made  
from ~~the Dacron~~ DACRON®. DACRON® is a registered trademark of E.I. Du  
Pont de Nemours and Company, Wilmington, Delaware, for its brand of  
condensation polymer polyester fiber made from ethylene glycol and  
15 terephthalic acid. Also the frame 10 may be formed in a wooden frame, and the  
screen 9 may be used silk as the same as usual, nylon, polyester, and stainless  
steel and the like.

In addition, the screen 9 is determined in consideration of a printing

machine, ink, etc., although the screen about four times as the number of lines is used basically. For example, the number of the screen lines per inch of the dot screen is approximately 120 mesh (lines) in the case of 30 lines; approximately 200 meshes in the case of 50 lines; and approximately 240 meshes in the case of 60 lines.

In this embodiment, the dot is formed in the shape of an ellipse and is used. Moreover the dot may be formed in the shape of a circle, lozenge, square, line, cross and the like. Furthermore, according to printed matter, the good shape and favorite shape may be used alternatively.

The screen plate 11 produced by the above manufacture method of the screen plates is used in order to print to the cloth such as a towel and clothes such as a T-shirt, a trainer, etc., a T-shirt in this embodiment as shown in FIG. 5, by a roller printing and the like.

With the adjusted screen angle, the generating of moire is prevented efficiently without interfering the dot and mismatching the screen angle in dot decomposition, and the high quality product can be obtained.

In addition, although T-shirt as the printed object is explained in this embodiment, the printed objects including sheet material and processed goods which are processed with papers, fiber, resin material, metal material, ceramics, glass, etc. may be used. For example, it may be printed on the surface of the can  
5 as shown in FIG. 6.

Moreover, the "Dragonfly" which is a mark for arranging direction of a pattern with the film 8 as usual is given to arbitrary positions.

Other embodiments of the present invention will now be described with reference to FIGS. 7-36. In FIGS. 7-36, the same components as in the first  
10 embodiment described above with reference to FIGS. 7-36 are designated by the same reference numerals and therefore will not be further explained in great detail.

A second embodiment of the present invention is shown in FIGS. 7 and 8. It is distinguished from the first embodiment in that the formation process 7 is  
15 replaced from another process 7A. In the step 7A, when the delicate gap arises at the screen angle set up at the moire prevention step 1, both the screen 9 and the positive film 8 or either one is horizontally rotated to the angle at which there is

no the moire condition. Then the screen 9 is fixed to the frame 10 in the position (angle) that there is no the moire screen 9 is fixed to the frame 10 in the position (angle) that there is no the moire condition, and a screen plate 11A is formed. A screen plate 11A according to the second embodiment has similar  
5 advantages to that according to the first embodiment.

In addition, when the screen angle is not set up, the screen 9 may be horizontally rotated to the angle which the moire is lost, the screen 9 may be fixed to the frame 10 in the position (angle) which the moire is lost, and the screen plate 11A may be created.

10 A third embodiment of the present invention is shown in FIGS. 9 to 14. It is distinguished from the first embodiment in that the moire prevention process 1 is replaced from another step 1A. In the moire prevention step 1A, the electronic correction processing is performed for the picture manuscript using the scanners X for making the plate and the like, and electronic data is processed suitably by  
15 the FM screen method which expresses a shade by the density without regularity of the dots infinitely formed. In the moire prevention step 1A, as shown in FIG. 10, In this moire prevention step 1A, the pattern as a manuscript is read with a scanner X as usual or the processed image data is used, and the data is divided by

four colors as the printing colors by digital decomposition, that is, cyan 2,  
magenta 4, yellow 5 and black 3 (S1). Then each divided color is converted by a  
monochrome-two gray scale, and the input and output resolutions are set the same  
value, and a conversion system is set as the error conversion spreading method  
5 (dither) (S2). After each color is changed into gray scale, and the size ratio is set  
as "1" (S3), each color changed into the gray scale is specified, and it piles up as  
one frame (S4) and is printed by the screen 9 by controlling of the terminal.

Thus, since a screen plate 11B according to the second embodiment has  
similar advantages to that according to the first embodiment and can reduce the  
10 size of dot, it can prevent degradation of the quality-of-image by the moire  
efficiently and can print high resolution over the whole grayscale from a highlight  
to a shadow.

In addition, as shown in FIG. 14, when the server Y having an input-and  
output means, a control means to perform a system based on a main program,  
15 various databases (DB) which memorize image data information, customer  
information, etc. and memory means (memory part), etc is set suitably, and it is  
connected to the communications network Z through radio or the telephone line,  
so that it can received the image data at any time from consumer terminals

including a plurality of the personal computers, a notebook typed PC, PDA, L-mode correspondence telephone, a portable telephone, and Internet-compatible household electric appliances which are connected through the communications network Z and the digital processing can be performed by the method of this  
5 embodiment. Therefore, it can be performed efficiently in a short time from data receipt to completion.

Furthermore, when the data obtained using electronic data processing is used as surface treatment information on the printed object, it combines with the conventional processing methods including the etching processing and sandblast  
10 processing so that the high resolution and high quality picture are reproducible to the printed object.

A fourth embodiment of the present invention is shown in FIGS. 15 to 20. It is distinguished from the third embodiment in that the moire prevention step 1 is replaced from another step 1B. In this moire prevention step 1B, the electronic  
15 data processing is performed by the special-color decomposition by the simulation. The moire prevention step 1B includes a step 13 for selecting, a step 14 for selecting colors, a step 15 for performing the spot colors, a step 16 for

converting and a step 17 performing a frame.

In the selection step 13, each color is chosen via the simulation by a syringe tool in means for specifying the color range after a based picture (RGB) 12 as the original edition is reproduced by data-processing terminal.

5 In the color selection step 14, each color chosen at the selection step 13 is saved as a selection range, and the resemble color to the picture 12 is selected.

In the spot-color performing step 15, the color chosen and determined at the color selection step 14 transposes to a spot color.

10 In the conversion step 16, the state that is determined at the spot color-performing step 15 is saved according to each color, and it is converted to the monochrome-two gray scale after it is converted to the gray scale.

In the frame processing step 17, each color is selected and piled up as one frame after the color selection process 14, the spot color processing step 15, and the conversion step 16 are processed successively.

15 In the selection step 13, when each color is chosen, the maximum



permissible quantity may be set up moderately, and automatic color range specification including red color, yellow color, green color, cyan color, blue color, magenta color, highlight, neutral colors, shadow, etc. may be used.

5 In the conversion step 16, the error conversion spreading method (dither) is used preferably, the setting value of the input resolution and output resolution is set up similarly, and it is performed.

A fifth embodiment of the present invention is shown in FIGS. 21 to 24. It is distinguished from the fourth embodiment in that the selection process 13 is replaced from another selection process 13A that comprises of an operation step 10 18, a saving step 19 and an amendment step 20.

In the operation step 18, the reproduced picture is performed by the operation processing after a based picture (RGB) 12 as the original edition is reproduced by data-processing terminal.

15 In the saving step 19, each color is chosen, reversed the gradation, and saved at a new channel.

In the amendment step 20, the gradation of the image data saved at the step 19 is amended at level.

Thus, a moire prevention step 1C chooses each color and can processes so that the moire prevention process 1C according to the fifth embodiment has similar advantages to that according to the fourth embodiment.

A sixth embodiment of the present invention is shown in FIGS. 25 to 36. It is distinguished from the fourth embodiment in that the moire prevention step 1A is replaced from another process 1D. In the moire prevention process 1D, the electronic data processing is performed by the special-color decomposition of full color. The moire prevention step 1D is comprised of a step 24 for forming an under base white, a step 27 for forming an top white, a step 28 for converting to index color, a step 29 for determining the number of colors, a step 30 for adding the colors, a step 31 for processing the index color, a step 34 for forming an under base white and a step 35 for finishing.

The forming step 24 further includes a step 21 for coping and pasting the reproduced picture after the based picture (RGB) 12 as the original edition is reproduced by data-processing terminal, and a new channel is created; a step 22

for reversing and converting the picture pasted at this copy step 21; and a step 23 for converting the picture to the monochrome-two gray scale and gray, and save to another name, for example, under base white.

5 The forming step 27 further includes a step 25 for selecting the white of a highlight portion, at the same time, the white portion in a picture is specified after the based picture (RGB) 12 as the original edition is reproduced by data-processing terminal; a step 26 for saving the picture as a new channel created; a step 23A for converting the picture saved in the saving step to the monochrome-two gray scale and gray, and save to another name, for example, top white.

10 In the index color conversion process 28, the picture (RGB) 12 as the original edition is changed into an index color by the error conversion spreading method (dither), noise method or the pattern method, dither in this embodiment.

In the number determination process 29, the number of colors is determined of the picture changed in the index color conversion process 28.

15 In the color addition step 30, the picture processed in the number determination process 29 is specified at the color range, and each color is

selected. Then each selected color is added to a new channel.

In the index color processing step 31, the top white and under base white saved in the top white forming step 27 and the under base white forming step 24 are added to the index color data after the color addition step 30 for every color is performed.

The under base white forming process 34 for utilizing the basic color further includes a step 32 for reversing; and a step 33 for converting. The reversing step 32 is performed to select the basic color (color of the background) from the picture (RGB) 12 and reverse the specified range. In the conversion step 33, the reversed picture is added to the new channel, and it performs the reversal conversion of gradation and is converted to the monochrome-two gray scale and gray scale.

The finish step 35 performs to add the under base white created in the under base white forming step 34 to the index color completed at the index color processing step 31.

When the base color is not printed, the moire prevention step 1D

according to the sixth embodiment has similar advantages to that according to the fourth embodiment.

Furthermore, although each embodiment differs mainly explained based on the first embodiment, even if it uses the present invention combining the composition used for the form of not only this but each embodiment, the same action effect is acquired.

As set forth above, the advantages of the invention are as follows:

(1) A method for manufacturing of a screen plate including the screen printing plate, screen printing plate using an image, electronic stencil and the like in order to print the image to printed object, includes a step for preventing generating of a moire including moire fringes and a spot produced by piling up the formation which the point and line are distributed regularly and geometrically, one of setting a dot angle of printing colors needed for printing of the screen plate at a predetermined angle for each color (e.g., cyan (C), magenta (M), yellow (Y), and black (K)) and matching a screen angle, which is the angle to which the screen itself is rotated, with the dot angle, in order to obtain a no moire condition; and a step for forming the screen plate including a screen and a frame stretching the screen so that it can prevent certainly the generating of

moire.

Therefore, it can print a picture with a lively motion and with high resolution.

(2) As discussed above, since it can prevent certainly the generating of  
5 moire, it can be manufactured the high utility value of a screen plate in the  
optimal state.

**Abstract**

~~A method for manufacturing of a screen plate including the screen printing plate, screen printing plate using an image, electronic stencil and the like in order to print the image to printed object, includes a step for preventing generating of a moire including moire fringes and a spot produced by piling up the formation which the point and line are distributed regularly and geometrically, one of setting a dot angle of printing colors needed for printing of the screen plate at a predetermined angle and matching a screen angle with the dot angle; and a step for forming the screen plate including a screen and a frame stretching the screen so that it can prevent certainly the generating of moire so that it can print a picture with a lively motion and with high resolution, and it can be manufactured the high utility value of a screen plate in the optimal state.~~

A method for manufacturing a screen plate having a screen printing plate which utilizes an image or an electronic stencil to print an image onto an object so as to prevent the generation of moire, including the occurrence of moire fringes and spots in the printed image, includes a step of forming an image in such a way that points and lines of the image are distributed regularly and geometrically, by setting a dot angle for each individual color in the printed image needed for printing the screen plate and matching a screen angle by rotating the screen to obtain a no moire condition; and a step of forming the

MARKED SPECIFICATION

F-7882

Ser. No. 10/614,640

screen plate having a screen and a frame for stretching the screen in such a way that generation of moire is prevented and a sharp, high resolution printed image is produced on the object.